

RW-L2.5



- ◆ **Safer**

Cobalt Free Lithium Iron Phosphate (LFP) Battery, safety and long lifespan, high efficiency and high-energy density.

- ◆ **Reliable**

Intelligent BMS, providing complete protection. Natural cooling, IP23, wide temperature range: -20°C to +55°C.

- ◆ **Flexible**

Modular design, easy to expand, Max. 32 units in parallel, Max. capacity of 82kWh. Suited to residential and commercial applications for increasing the self-consumption ratio.

- ◆ **Convenient**

Battery module auto networking, easy maintenance, support remotely monitoring and upgrade, support USB drive upgrade the firmware.

- ◆ **Eco-Friendly**

Use environmental protection materials, the whole module non-toxic, pollution-free.

- ◆ **Wall-Mounted**

Flat design, wall-mounted, saving installation space.

Model		RW-L2.5
Main Parameter		
Battery Chemistry	LiFePO ₄	
Capacity (Ah)	100	
Scalability	Max.32 pcs in Parallel(82kWh)	
Nominal Voltage (V)	25.6	
Operating Voltage(V)	21.6 ~ 28.8	
Energy (kWh)	2.56	
Usable Energy (kWh) ^[1]	2.30	
Charge/Discharge Current (A)	Recommend ^[2]	50
	Max. ^[2]	80
	Peak	105 (30s,25°C)
Other Parameter		
Recommend Depth of Discharge	90%	
Dimension (W/H/D, mm)	380*450*215(without Hanging Board)	
Weight Approximate(kg)	28	
Master LED Indicator	5LED(SOC:20%~SOC100%),3LED (working, alarming, protecting)	
IP Rating of Enclosure	IP23	
Operating Temperature	Charge:0~ +55°C / Discharge:-20°C~ +55°C	
Storage Temperature	0°C ~ +35°C	
Humidity	5%~95%	
Altitude	≤2000m	
Cycle Life	≥4000(25°C±2°C,0.2C/0.2C,90%DOD,70%EOL)	
Installation	Wall-Mounted	
Communication Port	CAN2.0, RS485	
Warranty Period ^[3]	5 years	
Energy Throughput ^[3]	4MWh@70%EOL	
Certification	UN38.3, MSDS	

[1] DC Usable Energy, test conditions: 90% DOD, 0.2C charge & discharge at 25°C. System usable energy may vary due to system configuration parameters.

[2] The current is affected by temperature and SOC.

[3] The warranty is due whichever reached first of warranty period or energy throughput.

Introduction

This series lithium iron phosphate battery is one of new energy storage products developed and produced by Deye , it can be used to support reliable power for various types of equipment and systems.

This series is especially suitable for application scene of low power, limited installation space, restricted load-bearing and long cycle life.

This series has built-in BMS battery management system, which can manage and monitor cells information including voltage, current and temperature. What's more, BMS can balance cells charging and discharging to extend cycle life.

Multiple batteries can connect in parallel for larger capacity and longer power supporting duration requirements.

